

SAFETY DATA SHEET



Date of Issuance/Date of Revision: 10/20/2018

Version Number: 1

Section 1: Identification

Product Name: **GLOSS**
Product Code: **TCP-018**
Other Means of Identification: Not Available.
Product Type: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use: Hobby Applications.
Use of the substance or mixture: Coating, Paints, or Painting-related materials
Uses advised against: Not applicable

Manufacturer: Tru-Color Paint
4220 West Opportunity Way
Suite 104
Phoenix, AZ 85086 USA

Emergency Telephone Number: Call U.S. Environmental Protection Agency's National Response Center
1 (800) 424-8802

Technical Phone Number: (714) 488-9779 (Phoenix, AZ) 8:00 a.m. - 5:00 p.m. (Arizona Standard Time)

Section 2: Hazards Identification

OSHA/HCS Status: This material is considered to be hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the Substance or Mixture: FLAMMABLE LIQUIDS- Category 2
SKIN IRRITATION- Category 2
EYE IRRITATION- Category 2A
CARCINOGENICITY- Category 2
TOXIC TO REPRODUCTION (Unborn Child)- Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic Effect)- Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS), hearing organs, kidneys, and liver)- Category 2
Percentage of the mixture consisting of ingredient(s) of unknown toxicity:
15.0% (Oral), 15.0% (Dermal), 21.3% (Inhalation)
Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8.)

GHS Label Elements

Hazard Pictograms:

Section 2: Hazards Identification



| | |
|-----------------------------------|---|
| Signal Word: | Danger |
| Hazard Statements: | Highly flammable liquid and vapor. Causes serious eye irritation. Causes skin irritation. Suspected of damaging the unborn child. Suspected of causing cancer. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. (Central nervous system (CNS), hearing organs, kidneys, liver) |
| <u>Precautionary Statements</u> | |
| Prevention: | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink, or smoke when using this product. Wash hands thoroughly after handling. |
| Response: | Get medical attention if you feel unwell. ID exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POSION CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irradiation persists: Get medical attention. |
| Storage: | Store locked up. Store in well-ventilated place. Keep cool. |
| Disposal: | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental Label Elements: | Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated. |
| Hazards Not Otherwise Classified: | Prolonged or repeated contact may dry skin and cause irritation. |

Section 3: Composition/Information on Ingredients

| | |
|-----------------------|--------------|
| Substance or Mixture: | Mixture |
| Product Name: | <u>Gloss</u> |

Product Name: GLOSS

| Ingredient Name | % | CAS Number |
|--------------------------------|---------------|------------|
| Isopropyl alcohol | ≥ 16.5 - ≤ 33 | 67-63-0 |
| Toluene | ≥ 7 - ≤ 12 | 108-88-3 |
| Xylene | ≥ 3 - ≤ 9.4 | 1330-20-7 |
| Acetone | ≥ 16.5 - ≤ 33 | 67-64-1 |
| n-Butyl Acetate | ≥ 2 - ≤ 7 | 123-86-4 |
| 4-hydroxy-4-methylpentan-2-one | ≥ 17 - ≤ 26 | 123-42-2 |
| Ethylbenzene | ≤ 1.3 | 100-41-4 |
| Butanone | ≥ 3 - ≤ 7.5 | 78-93-3 |
| Methyl Methacrylate | ≤ 0.5 | 80-62-6 |
| n-Butyl Methacrylate | ≤ 0.5 | 97-88-1 |

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to the health or the environment and hence require reporting in this section.

Occupational Exposure limits, if applicable, are listed in section 8.

Section 4: First Aid Measures

If ingestion, irritation, and type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

| | |
|---------------|--|
| Eye Contact: | Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. |
| Inhalation: | Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin Contact: | Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleaner. Do NOT use solvents or thinners. |
| Ingestion: | If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting. |

Most important symptoms/effects, acute and delayed

Potential acute health effects

| | |
|---------------|---|
| Eye Contact: | Causes serious Eye irritation. |
| Inhalation: | Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. |
| Skin Contact: | Causes Skin irritation. Defatting to the skin. |
| Ingestion: | Can cause central nervous system (CNS) depression. |

Over-exposure signs/symptoms

| | |
|--------------|--|
| Eye Contact: | Adverse Symptoms may include the following: Pain or irritation Watering Redness |
| Inhalation: | Adverse Symptoms may include the following: Nausea or vomiting Headache |

Section 4: First Aid Measures

Drowsiness or fatigue
Dizziness or vertigo
Unconsciousness
Reduced fetal weight
Increase in fetal deaths
Skeletal malformations

Skin Contact: Adverse Symptoms may include the following:
Irritation
Redness
Dryness
Cracking
Reduced fetal weight
Increase in fetal deaths
Skeletal malformations

Ingestion: Adverse Symptoms may include the following:
Reduced fetal weight
Increase in fetal deaths
Skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatment: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5: Fire-fighting Measures

Extinguishing media

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Do not use water jet.

Specific hazards arising from the chemical:

Highly flammable liquid or vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products:

Decomposition products may include the following materials: carbon oxides.

Special protective actions for fire-fighters:

Promptly isolate the scene by removing all persons from the vicinity of the accident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from the area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Section 5: Fire-fighting Measures

Special protective equipment for fire-fighters:

Fire fighters should wear protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental Precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, if water-insoluble, absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material (e.g. sand, earth vermiculite or diatomaceous earth) and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7: Handling and Storage

Protective measures: Put on appropriate personal protective equipment (see Section 8). Avoid exposure- obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get into eyes or on skin or clothing. Do not breath vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Section 7: Handling and Storage

Special precautions:

Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities:

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8: Exposure Controls/Personal Protection

Control Parameters

Occupational exposure limits

| Ingredient Name | Exposure Limits |
|-------------------|---|
| Isopropyl alcohol | ACGIH TLV (United States, 3/2017). STEL: 400 ppm, 15 minutes TWA: 200 ppm, 8 hours OSHA PEL (United States, 6/2016). TWA: 980 mg/m ³ 8 hours TWA: 400 ppm 8 hours. |
| Toluene | OSHA PEL Z2 (United States, 2/2013). AMP: 500 ppm 10 minutes CEIL: 300 ppm TWA: 200 ppm 8 hours. ACGIH TLV (United States, 3/2017). TWA: 20 ppm 8 hours. |
| Xylene | ACGIH TLV (United States, 3/2017). STEL: 651 mg/m ³ 15 minutes STEL: 150 ppm 15 minutes TWA: 434 mg/m ³ , 8 hours TWA: 100 ppm 8 hours. OSHA PEL (United States, 6/2016). TWA: 435 mg/m ³ 8 hours TWA: 100 ppm 8 hours. |
| Acetone | ACGIH TLV (United States, 3/2017). STEL: 500 ppm 15 minutes TWA: 250 ppm 8 hours. OSHA PEL (United States, 6/2016). TWA: 2400 mg/m ³ 8 hours TWA: 1000 ppm 8 hours. |
| n-Butyl Acetate | OSHA PEL (United States, 6/2016). TWA: 710 mg/m ³ 8 hours TWA: 150 ppm 8 hours. ACGIH TLV (United States, 3/2017). |

Product Name: GLOSS

| | |
|--------------------------------|---|
| | STEL: 150 ppm 15 minutes TWA: 50 ppm 8 hours. |
| 4-hydroxy-4-methylpentan-2-one | ACGIH TLV (United States, 3/2017). TWA: 238 mg/m ³ 8 hours TWA: 50 ppm 8 hours. OSHA PEL (United States, 6/2016). TWA: 240 mg/m ³ 8 hours TWA: 50 ppm 8 hours. |
| Ethylbenzene | ACGIH TLV (United States, 3/2017). TWA: 20 ppm 8 hours. OSHA PEL (United States, 6/2016). TWA: 435 mg/m ³ 8 hours TWA: 100 ppm 8 hours. |
| Butanone | ACGIH TLV (United States, 3/2017). STEL: 885 mg/m ³ 15 minutes STEL: 300 ppm 15 minutes TWA: 590 mg/m ³ 8 hours TWA: 200 ppm 8 hours. OSHA PEL (United States, 6/2016). TWA: 590 mg/m ³ 8 hours TWA: 200 ppm 8 hours. |
| Methyl Methacrylate | ACGIH TLV (United States, 3/2017). Skin Sensitizer STEL: 100 ppm 15 minutes TWA: 50 mg/m ³ 8 hours. OSHA PEL (United States, 6/2016). TWA: 410 mg/m ³ 8 hours TWA: 100 ppm 8 hours. |
| n-Butyl Methacrylate | IPEL (PPG). TWA: 50 ppm STEL: 75 ppm. |

Key to abbreviations

| | | | |
|--------|---|-------|----------------------------------|
| A= | Acceptable Maximum Peak | S= | Potential Skin Absorption |
| ACGIH= | American Conference of Governmental Industrial Hygienists | SR= | Respiratory Sensitization |
| C= | Ceiling Limit | SS= | Skin Sensitization |
| F= | Fume | STEL= | Short-term Exposure Limit Values |
| IPEL= | Internal Permissible Exposure Limit | TD= | Total Dust |
| OSHA= | Occupational Safety and Health Administration | TLV= | Threshold Limit Value |
| R= | Respirable | TWA= | Time Weighted Average |
| Z= | OSHA 29 CFR 1910.1200 Subpart Z- Toxic and Hazardous Substances | | |

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls: Use only with adequate ventilation. Use appropriate enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls: Emissions from ventilation of work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering

Section 8: Exposure Controls/Personal Protection

modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection:

Chemical splash goggles.

Skin protection

Hand protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves:

For prolonged or repeated handling, use the following type of gloves:

Recommended: Butyl rubber, polyvinyl alcohol (PVA), Viton®

May be used: Nitrile rubber.

Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling the product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection:

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9: Physical and Chemical Properties

Appearance

Physical state:

Liquid.

Color:

Not Available.

Odor:

Not Available.

Odor threshold:

Not Available.

pH:

Not Available.

Melting point:

Not Available

Section 9: Physical and Chemical Properties

| | |
|---|--|
| Boiling point: | > 37.78°C (> 100°F) |
| Flash point: | Open cup: -6.67°C (20°F) |
| Auto-ignition temperature: | Not Available. |
| Decomposition temperature: | Not Available. |
| Flammability (For solid, gas): | Not Available. |
| Lower and Upper Explosive (flammable) limits: | Lower: 1.9% |
| Evaporation rate: | 3.41 (butyl acetate = 1) |
| Vapor pressure: | 8.8kPa (66.0 mm Hg)[room temperature] |
| Vapor density: | Not Available. |
| Relative density: | 0.81 |
| Density (lbs/gal): | 7.40 |
| Solubility: | Insoluble in the following materials: cold water. |
| Partition coefficient: n-octanol/water: | Not Available. |
| Viscosity: | Kinematic (40° C (104° F)): > 0.21 cm ² /s (> 21 CSt) |
| Volatility: | 92% (v/v), 88.47% (w/w) |
| % Solid. (w/w): | 11.53 |

Section 10: Stability and Reactivity

| | |
|-------------------------------------|--|
| Reactivity: | No specific test data related to reactivity available for this product or its ingredients. |
| Chemical stability: | This product is stable. |
| Possibility of hazardous reactions: | Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid: | When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. |
| Incompatible materials: | Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. |
| Hazardous decomposition products: | Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. |

Section 11: Toxicological InformationInformation on toxicological effectsAcute toxicity

| Product/Ingredient Name | Result | Species | Dose | Exposure |
|-------------------------|-----------------------|---------|-------------------------|----------|
| Isopropyl Alcohol | LC50 Inhalation Vapor | Rat | 72600 mg/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | 12800 mg/kg | --- |
| | LD50 Oral | Rat | 4.396 g/kg | --- |
| Toluene | LC50 Inhalation Vapor | Rat | 49 g/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | 8.39 g/kg | --- |
| | LD50 Oral | Rat | 636 mg/kg | --- |
| Xylene | LD50 Dermal | Rabbit | > 1.7 g/kg | --- |
| | LD50 Oral | Rat | 4.3 g/kg | --- |
| Acetone | LC50 Inhalation Vapor | Rat | 76000 mg/m ³ | 4 hours |

Product Name: GLOSS

| | | | | |
|--------------------------------|--|------------------------------|---|----------------------------------|
| | LD50 Dermal LD50 Oral | Rabbit Rat | 20 g/kg 1.8 g/kg | --- --- |
| n-Butyl Acetate | LC50 Inhalation Vapor LC50 Inhalation Vapor LD50 Dermal LD50 Oral | Rat Rat Rabbit Rat | > 21.1 mg/l 2000 ppm > 17600 mg/kg 10.768 g/kg | 4 hours 4 hours --- --- |
| 4-hydroxy-4-methylpentan-2-one | LD50 Dermal LD50 Oral | Rabbit Rat | 13500 mg/kg 2520 mg/kg | --- --- |
| Ethylbenzene | LC50 Inhalation Vapor LD50 Dermal LD50 Oral | Rat Rabbit Rat | 17.8 mg/l 17.8 g/kg 3.5 g/kg | 4 hours --- --- |
| Butanone | LC50 Inhalation Vapor LD50 Dermal LD50 Oral | Rat (mg/kg) Rabbit Rat | 11243 ppm 6480 mg/kg 2737 mg/kg | 4 hours --- --- |
| Methyl Methacrylate | LC50 Inhalation Vapor LD50 Dermal LD50 Oral | Rat Rabbit Rat | 78000 mg/m ³ > 5 g/kg 7872 mg/kg | 4 hours --- --- |
| n-Butyl Methacrylate | LC50 Inhalation Gas LC50 Inhalation Vapor LD50 Dermal LD50 Oral | Rat Rat Rabbit Rat | 4910 ppm 29000 mg/m ³ 10.2 g/kg 16 g/kg | 4 hours 4 hours --- --- |

Conclusion/Summary: There are no data on the mixture itself.

Irritation/Corrosion

| Product/Ingredient Name | Result | Species | Score | Exposure | Observation |
|-------------------------|-------------------------|---------|-------|-----------------|-------------|
| Xylene | Skin- Moderate irritant | Rabbit | --- | 24 hours 500 mg | --- |

Conclusion/Summary

Skin: There are no data available on the mixture itself.
 Eyes: There are no data available on the mixture itself.
 Respiratory: There are no data available on the mixture itself.

SensitizationConclusion/Summary

Skin: There are no data available on the mixture itself.
 Respiratory: There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Classification

| Product/Ingredient Name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Isopropyl Alcohol | --- | 3 | --- |
| Toluene | --- | 3 | --- |
| Xylene | --- | 3 | --- |
| Ethylbenzene | --- | 2B | --- |
| Methyl Methacrylate | --- | 3 | --- |

Carcinogen Classification Code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen.

OSHA: +

Not listed/not regulated: -

Section 11: Toxicological InformationReproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Name | Category |
|---------------------------------|------------|
| Isopropyl Alcohol | Category 3 |
| Toluene | Category 3 |
| Xylene | Category 3 |
| Acetone | Category 3 |
| n-Butyl Acetate | Category 3 |
| 4-hydroxy-4-methylpentane-2-one | Category 3 |
| Butanone | Category 3 |
| Methyl Methacrylate | Category 3 |
| n-Butyl Methacrylate | Category 3 |

Specific target organ toxicity (repeated exposure)

| Name | Category |
|----------------------|------------|
| Toluene | Category 2 |
| Xylene | Category 2 |
| Ethylbenzene | Category 2 |
| n-Butyl Methacrylate | Category 2 |

Target organs

Contains material which causes damage to the following organs: brain.
Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, the reproductive system, liver, heart, spleen, peripheral nervous system, gastrointestinal tract, upper respiratory tract, skin, central nervous system (CNS), ears, eye, lens or cornea, testes.

Aspiration hazard

| Name | Result |
|--------------|-------------------------------|
| Toluene | ASPIRATION HAZARD- Category 1 |
| Xylene | ASPIRATION HAZARD- Category 1 |
| Ethylbenzene | ASPIRATION HAZARD- Category 1 |

Information on the likely routes of exposure

Potential acute health effects

Eye contact: Causes serious eye irritation.

Inhalation: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Skin contact: Causes skin irritation. Defatting to the skin.

Ingestion: Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:
Pain or irritation
Watering
Redness

Inhalation: Adverse symptoms may include the following:
Nausea or vomiting
Headache
Drowsiness/fatigue

Section 11: Toxicological Information

Dizziness/vertigo
 Unconsciousness
 Reduced fetal weight
 Increase in fetal deaths
 Skeletal malformations

Skin contact:

Adverse symptoms may include the following:

Irritation
 Redness
 Dryness
 Cracking
 Reduced fetal weight
 Increase in fetal deaths
 Skeletal malformations

Ingestion:

Adverse symptoms may include the following:

Reduced fetal weight
 Increase in fetal weight
 Skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary:

There are no data available on the mixture itself. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering control (see Section 8.) Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short-term exposure

Potential immediate effects:

There are no data available on the mixture itself.

Potential delayed effects:

There are no data available on the mixture itself.

Long-term exposure

Potential immediate effects:

There are no data available on the mixture itself.

Potential delayed effects:

There are no data available on the mixture itself.

Potential chronic health effects

General:

Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity:

Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity:

No known significant effects or critical hazards.

Section 11: Toxicological Information

| | |
|------------------------|---|
| Teratogenicity: | Suspected of damaging the unborn child. |
| Developmental effects: | No known significant effects or critical hazards. |
| Fertility effects: | No known significant effects or critical hazards. |

Numerical measures of toxicityAcute toxicity estimates

| Route | ATE Value |
|------------------------------|--------------|
| Oral | 7559.6 mg/kg |
| Dermal | 7462.0 mg/kg |
| Inhalation (gases) | 23585.0 ppm |
| Inhalation (vapors) | 60.95 mg/l |
| Inhalation (dusts and mists) | 7.900 mg/l |

Section 12: Ecological InformationToxicity

| Product/ingredient name | Result | Species | Exposure |
|---------------------------------|--|--|----------|
| Isopropyl Alcohol | Acute EC50 10100 mg/l Fresh water | Daphnia- Daphna Magna | 48 Hours |
| 2-methoxy-1-methylethyl acetate | Acute LC50 161 mg/l Fresh water | Fish | 96 Hours |
| Ethylbenzene | Acute LC50 150 to 200 mg/l Fresh water | Fish- Lepornis macrochirus- Young of the year | 96 Hours |

Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Acetone | --- | --- | Readily |
| Toluene | --- | --- | Readily |
| Xylene | --- | --- | Readily |
| Ethylbenzene | --- | --- | Readily |

Bioaccumulative potential

| Product/ingredient name | Log P _{ow} | BCF | Potential |
|--------------------------------|---------------------|-------------|-----------|
| Isopropyl Alcohol | 0.05 | --- | Low |
| Acetone | -0.24 | 3 | Low |
| Toluene | 2.73 | 8.32 | Low |
| Xylene | 3.16 | 7.4 to 18.5 | Low |
| n-Butyl Acetate | 1.78 | --- | Low |
| 4-hydroxy-4-methylpentan-2-one | -0.14 to 1.03 | --- | Low |
| Ethylbenzene | 3.15 | 79.43 | Low |
| Butanone | 0.29 | --- | Low |
| Methyl Methacrylate | 1.38 | --- | Low |
| n-Butyl Methacrylate | 2.88 | --- | Low |

Mobility in soil

Soil/water coefficient (K_{oc}): Not available.

Section 13: Disposal Considerations

Disposal methods: The generation of waste should be avoided or minimized whatever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should be considered when recycling is

Section 13: Disposal Considerations

not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures.

Section 14: Transport Information

| | DOT | IMDG | IATA |
|-----------------------------|--------------------|-----------------|-----------------|
| UN Number | UN 1263 | UN 1263 | UN 1263 |
| UN proper shipping name | PAINT | PAINT | PAINT |
| Transport hazard class(es) | 3 | 3 | 3 |
| Packing group | II | II | II |
| Environmental hazards | No. | No. | No. |
| Marine pollutant substances | Not Applicable. | Not Applicable. | Not Applicable. |
| Product RQ (lbs.) | 891.8 | Not Applicable. | Not Applicable. |
| RQ substances | (xylene , toluene) | Not Applicable. | Not Applicable. |

Additional Information

DOT: Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

IMDG: None identified.

IATA: None identified.

Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15: Regulatory InformationUnited States

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304

SARA 304 RQ: Not Applicable

Composition/information on ingredients

No products were found.

SARA 311/312

Classification: FLAMMABLE LIQUIDS- Category 2
SKIN IRRITATION- Category 2
EYE IRRITATION- Category 2A
CARCINOGENICITY- Category 2
TOXIC TO REPRODUCTION (Unborn Child)- Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)- Category 3

Section 15: Regulatory Information

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS), hearing organs, kidneys, liver)- Category 2
HNOC- Defatting irritant

Composition/information on ingredients

| Name | % | Classification |
|--------------------------------|-----------------------|--|
| Isopropyl Alcohol | $\geq 16.5 - \leq 33$ | FLAMMABLE LIQUIDS- Category 2 EYE IRRITATION- Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)- Category 3 |
| Toluene | $\geq 7 - \leq 12$ | FLAMMABLE LIQUIDS- Category 2 SKIN IRRITATION- Category 2 TOXIC TO REPRODUCTION (Unborn Child)- Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)- Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE)- Category 2 ASPIRATION HAZARD- Category 1 HNOC- Defatting Irritant |
| Xylene | $\geq 3 - \leq 9.4$ | FLAMMABLE LIQUIDS- Category 3 ACUTE TOXICITY (dermal)- Category 4 ACUTE TOXICITY (inhalation)- Category 4 SKIN IRRITATION- Category 2 EYE IRRITATION- Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)- Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS), kidneys, liver)- Category 2 ASPIRATION HAZARD- Category 1 |
| Acetone | $\geq 16.5 - \leq 33$ | FLAMMABLE LIQUIDS- Category 2 EYE IRRITATION- Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)- Category 3 HNOC- Defatting Irritant |
| n-Butyl Acetate | $\geq 2 - \leq 7$ | FLAMMABLE LIQUIDS- Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)- Category 3 HNOC- Defatting Irritant |
| 4-hydroxy-4-methylpentan-2-one | $\geq 17 - \leq 26$ | FLAMMABLE LIQUIDS- Category 3 EYE IRRITATION- Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)- Category 3 |
| Ethylbenzene | ≤ 1.3 | FLAMMABLE LIQUIDS- Category 2 ACUTE TOXICITY (inhalation)- Category 4 CARCINOGENICITY- Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs)- Category 2 ASPIRATION HAZARD- Category 1 HNOC- Defatting Irritant |
| Butanone | $\geq 3 - \leq 7.5$ | FLAMMABLE LIQUIDS- Category 2 EYE IRRITATION- Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)- Category 3 HNOC- Defatting Irritant |
| Methyl Methacrylate | ≤ 0.5 | FLAMMABLE LIQUIDS- Category 2 SKIN IRRITATION- Category 2 SKIN SENSITIZATION- Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory Tract Irritation)- Category 3 HNOC- Defatting Irritant |

Product Name: GLOSS

| Name | % | Classification |
|----------------------|-------|--|
| n-Butyl Methacrylate | ≤ 0.5 | FLAMMABLE LIQUIDS- Category 3 ACUTE TOXICITY (Inhalation)- Category 4 SKIN IRRITATION- Category 2 EYE IRRITATION- Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory Tract Irritation)- Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (central nervous system (CNS), kidneys, liver)- Category 2 HNOC- Defatting Irritant |

SARA 313

| | <u>Chemical Name</u> | <u>CAS Number</u> | <u>Concentration</u> |
|------------------------|----------------------|-------------------|----------------------|
| Supplier notification: | Toluene | 108-88-3 | 7 -13 |
| | Xylene | 1330-20-7 | 3 - 9.4 |
| | Ethylbenzene | 100-41-4 | ≤ 1.3 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop. 65

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

Section 16: Other Information

Hazardous Material Information System (U.S.A.)

Health: 2 * Flammability: 3 Physical Hazards: 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® and the associated label are not required on SDS's or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

This customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health: 2 Flammability: 3 Instability: 0

Date of Previous Issue: **No previous validation**

Organization that prepared the SDS: Tru-Color Paint

Key to Abbreviations:

- ATE= Acute Toxicity Estimate
- BCF= Bioconcentration Factor
- GHS= Globally Harmonized System of Classification and Labeling of Chemicals
- IATA= International Air Transport Association
- IBC= Intermediate Bulk Container
- IMDG= International Maritime Dangerous Goods
- LogP_{ow}= Logarithm of the octanol/water partition coefficient
- MARPOL= International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 ("Marpol" = marine pollution)
- UN= United Nations

+ Indicates information that has changed from previously issued versions.

Disclaimer:

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Tru-Color Paint, and to recommend precautionary measures for the storage and handling of products. No warranty or guarantee is given in

Section 16: Other Information

respect of the properties of products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.